

# ECOSMALL 70 L



SPECIFICHE PRINCIPALI	ECOSMALL 55	ECOSMALL 70
Larghezza utile di lavoro [ mm ] / Ycrubbing width / Largeur de nettoyage	550	700
Rendimento Orario max (mq/h) / Clening capacity un to / Rendement jusqu'à	2750	3250
Autonomia di lavoro max. (h) / operating range / Autonomie	3 - 3,5	3 - 3,5
Capacità Serbatoio Soluzione (lt) / Solution tank capacity / Capacité réservoir solution	70	70
Capacità Serbatoio Recupero (lt) / Recovery tank capacity / Capacité réservoir récupération	70	70
Velocità di avanzamento (Km/h) / Forward speed / Vitesse d'avancement	5	5
Pendenza superabile a pieno carico [%] / Max. slope / pente max. surmontable	10	10
Depressione (mBar) / Water lift / Dèpression	145	145
Pressione testata spazzole (kg) / Brush pressure / Pression des brosses	20	20
Rumorosità (dB) / Noise level / Bruit	73	73

SPECIFICHE DI ALIMENTAZIONE	ECOSMALL 55	ECOSMALL 70
Motore Trazione / Traction motor / Moteur traction	transaxle 200 W	transaxle 200 W
Motore Aspirazione (W) / Vacuum motor / Moteur d'aspiration	350	350
Motore Spazzola (W) / Brush motor / Moteur des brosses	400	450
Alimentazione (V) / Voltage / Alimentation	48	48
Batteria Trazione / Traction batteries / Batteries traction	4x12 V - 72 A/h	4x12 V - 72 A/h
Caricabatteria [a bordo] / Battery charger on borde / Chargeur de batterie incorporè	48V - 18/20 A	48V - 18/20 A
DIMENSIONI E PESI	ECOSMALL 55	ECOSMALL 70
Misure: LxIxh (mm) / Measures: Lxwxh / Mesures: LxIxh	1200X600X1100	1200X750X1100
Spazzole / Brush / Brosses	1x Ø 550	2x Ø 370
Larghezza (mm) / Squeegee / Largeur	790	870
Peso Macchina a Vuoto (kg) / Weight of the machine / Poids de la machine	87	92
Peso Batterie (Kg) / Weight of the batteries / poids des batteries	4x20	4x20