



fiorentini
WWW.FIORENTINISPA.COM

I 115




1300mm

2100 mm



1400mm



CARATTERISTICHE TECNICHE / TECHNICAL SPECIFICATION / CARACTÉRISTIQUES TECHNIQUES		I 115 SSB	I 115 SS G/D
larghezza utile lavoro / cleaning path / largeur de lavage	mm	1150	1150
rendimento orario max / scrubbing coverage rate / rendement théorique	mq/h	6900	8050
autonomia di lavoro max / battery run time / temps de travail max	H	3	/
capacità serbatoio gas /diesel / diesel fuel/lpg tank capacity / capacité réservoir gaz/diesel	L	/	20
capacità serbatoio soluzione / solution tank capacity / réservoir solution	L	210	210
capacità serbatoio recupero / recovery tank capacity / réservoir récupération	L	220	220
capacità contenitore rifiuti / waste tank capacity / capacité réservoir déchets	L	210	210
pista spazzante con spazzole laterali / cleaning path with 2 side brushes / piste de balayage avec 2 brosses latérales		1450	1450
superficie filtrante / filtering surface / surface filtrante		6	6
trazione / traction method/ traction		1 hydraulic motor	1 hydraulic motor
velocità di avanzamento / forward speed / vitesse	km/h	0-6	0-6
max pendenza / gradeability (ramp climb) / max. pente	%	10	10
depressione / vacuum water lift/ dépression	mBr	176	176
pressione testata spazzole / brush or pad down pressure / pression des brosses	kg	180	180
rumorosità / sound level / niveau sonore	dB	75	75
corridoio di sterzata / minimum aisle turn / couloir pour demi-tour	mm	1900	1900
SPECIFICHE ALIMENTAZIONE / SYSTEM VOLTAGE SPECIFICATIONS / DONNÉE DE L'ALIMENTATION			
potenza motore / motor power / puissance moteur		/	Gas/ diesel/GPL 28cv 20,5kw
motore lavaggio / wash / suction motor/ moteur d'aspiration de lavage		2x36v 500w	2x36v 500w
motore di aspirazione /suction motor/ moteur aspiration		1x36v 500w 3500 rpm	1x36v350w 3500rpm
motore spazzola / brush motor/ moteur brosse		3x36v 900w	3x OMM 80 idra.
motore scuotifiltro /filter shaker motor/ moteur secoue-filtre		1x 36v 4.3A 7000rpm	1x 36v 4.3A 7000rpm
motore trazione /traction motor/ moteur traction		idraulic GLT 400	idraulic GLT 400
alimentazione / system voltage / alimentation		Batt. 36v 630 Amp/h	/
batteria / battery / batterie		36v 630 A	/
DIMENSIONI / DIMENSIONS / DIMENSIONS			
Misure: lxlxh / Dimensions: lwxht / Dimensions : lxlxh	mm	2100	2100
larghezza spazzole / brush width/ largeur brosse	mm	1200	1200
diametro spazzole/ brush diameter / diamètre de la brosse	mm	3XØ380	3XØ380
altezza con roll bar / max height with roll bar mounted / hauteur avec roll bar	mm	1850	1850
altezza senza roll bar / max height without roll bar / hauteur sans roll bar	mm	1420	1420
spazzola centrale / central brush / brosse centrale	mm	Ø300X850	Ø300X850
spazzola laterale / side brush / brosse latérale	mm	2XØ550	2XØ550
tergi pavimento / squeegee / suceur	mm	1350	1350
peso macchina a vuoto / weight (without batteries) / poids (sans batteries)	kg	960	980
peso batteria / battery weight / poids de la batterie	kg	644	/



Ing.O.Fiorentini s.p.a
sede amm. e stabilimenti



50033 Piancaldoli (FI) via Piancaldoli 1896 Firenzuola
50033 Pietramala (FI) via pietramala 70/B
40024 Castel San Pietro (BO) via Cà Bianca 231/C

tel +39 0558173610 - fax +39 055817144
tel +39 055813447 - fax +39 055813504
tel +39 051941743 - fax +39 0516942400

filiali

20132 Milano via Palmanova 211/A
00012 Guidonia Montecelio (Roma) via Bruno Pontecorvo 20

tel +39 0227207783 - fax +39 022592779
tel +39 0774357184 - fax +39 0774353419