



Model	Lumen	Svjetlosna pokrivenost
4x320W MultiLED	166200	5000 mq
6x160W MultiLED	122100	4200 mq
4x160W MultiLED	81400	3300 mq

PERFORMANSE	FENIX 1500	FENIX 3000
Radna frekvencija	50-60 Hz	50-60 Hz
Radna snaga	110/230 VAC	110/230 VAC
Radna snaga	3,5 kVA	4,2 kVA
Radna temperatura	-30/+55 °C	-30/+55 °C
Nivo buke	65 dB	70 dB
MOTOR	Kohler KDW702	Kohler 15LD350
Radni okretaji	1500 rpm	3000 rpm
Hlađenje	Liquid	Air
Broj cilindara	2	1
Emisijski razred	Stage V	Stage V
ALTERNATOR		
Model	Linz Alumen	Linz Alumen
Izlazna snaga	3,5 kVA	4,2 kVA
Podešavanje	Brushless	Brushless
POTROŠNJA		
Rezervoar	100 l	40 l
Pogonsko gorivo	Diesel	Diesel
Autonomija	182 h	73 h
Potrošnja	0,55 l/h	0,55 l/h
CENTRALNA JEDINICA	DSE32010	DSE32010
Dodatna snaga	1,2 kVA	1,2 kVA
Dodatna oprema kao standard	1x230V 16A socket emergency push button	1x230V 16A socket emergency push button
GALVANIZIRANI STUP		
Sistem podizanja stupa	Manual	Manual
Okret	350°	350°
Maksimalna visina	8.5 m	8.5 m
Maksimalni udar vjetra od:	110 km/h	110 km/h
POKLOPAC I PRIKOLICA		
Prikolica	Lagana prikolica	Lagana prikolica
Osovina	Gumena suspenzija	Gumena suspenzija
Kotači	155/80R13	155/80R13
Baza	Bunded base 120%	Bunded base 120%
Stabilizatori	4 +1	4 +1
Poklopac	Powder coating paint	Powder coating paint
TRANSPORTNE DIMENZIJE		
Dimenzije	80x120x235 cm	80x120x235 cm
Težina	560 kg	470 kg